



EXPLOSION
PROOF **EX**



3268EX-ALC

EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

| | | |
|----------------------------|----------------------|--------------|
| Working Height | 38 ft | 11.6 m |
| Raised Platform Height | 32 ft | 9.8 m |
| Lowered Platform Height | 54 in | 1.37 m |
| Platform Size (inside) | 56 × 96 in | 1.4 × 2.44 m |
| Capacity (Overall) | 1,000 lbs | 454 kg |
| Overall Width | 69.5 in | 1.76 m |
| Overall Length | 107 in | 2.72 m |
| Stowed Height (Rails Up) | 99 in | 2.51 m |
| Stowed Height (Rails Down) | 69 in | 1.75 m |
| Deck Extension | 5 ft | 1.52 m |
| Ground Clearance | 8 in | 0.20 m |
| Maximum Drive Height | Full Height | |
| Wheelbase | 80.5 in | 2.04 m |
| Inside Turning Radius | 60 in | 1.52 m |
| Outside Turning Radius | 156 in | 3.96 m |
| Drive Speed (Stowed) | 3.8 mph | 6.1 km/h |
| Drive Speed (Raised) | 0.4 mph | 0.6 km/h |
| Gross Weight | 9,600 lbs | 4,354 kg |
| Batteries | 8 × 6V 420 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |

Specifications subject to change

S SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E STANDARD EQUIPMENT

- 32 ft Platform Height
- 38 ft Working Height
- 56 × 96 in Platform Size
- 8 in Ground Clearance
- 1,000 lb Capacity
- 5 ft Extendable Deck
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm
- Enhanced Padded Aircraft Rails
- Power Extension Deck
- EX Rated LED Task Lighting

O OPTIONAL

- Padded Aircraft Rails
- 1/2" Airline to Platform
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Scissor Stack Bellow

MSRP: \$314,247

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com